

# Code Blue®

## DIGITAL GSM CELLULAR SYSTEM PRODUCT SPECIFICATION

### 1.0 GENERAL

The Code Blue Digital GSM Cellular System shall be capable of being used with any Code Blue model CB 1 or CB 8 emergency speakerphone that is outdoors and free of signal obstruction. The system shall consist of an internally mounted cellular interface module, an internal or external antenna, and a cable that connects the interface module to the antenna. A subscription to a local cellular carrier shall be required by the end user, and a separate contract, phone number and SIM card shall be obtained for each unit purchased. The local cellular service provider shall provide the SIM card for activation.

### 2.0 CELLULAR INTERFACE SPECIFICATIONS, GSM

RF connection	TNC
Frequency Range	850/1900 MHz
Operating Voltage	12 VDC
Type	modular cellular connection interface
Connection	RJ11C
Operating temperatures	-10F to +122F (-23C to +50C)
Operating humidity	to 95% (no condensing)

### 3.0 WARRANTY

The unit shall be warranted for a period of one year. Reference manufacturer's warranty for further details.

### 4.0 MANUFACTURER

- 4.1 The Manufacturer shall be Code Blue Corporation of Holland, Michigan. There are no equivalents.
- 4.2 Code Blue Corporation manufactures its products according to the most recent revision of product specifications, and shall not be held responsible for obsolete or outdated specifications. For the latest revision, please refer to [www.codeblue.com](http://www.codeblue.com).