

Second Opening Options

STANDARD/CUSTOM PLATE

The standard, blank stainless steel plate that accompanies each CB 1-d, CB 4-d and CB 9-d model can easily have the company, university, agency, etc. logo applied; an effective enhancement of brand recognition.

Code Blue can also supply a specified custom stainless steel plate assembly for the second opening in the faceplate. A detailed drawing showing the required dimensions must be forwarded to Code Blue for review and approval.

CAMERA ENCLOSURE

Code Blue can supply a standard camera enclosure assembly for the second opening in the faceplate on the CB 1-d, CB 4-d, and CB 9-d. This assembly includes the stainless steel faceplate, face plate gasket, camera housing (face plate and junction box), camera housing gasket and McGard® security screws.

Mini board camera and camera mounting bracket are supplied by others or can be ordered from Code Blue as a special order.

DIRECTORY ASSEMBLY

A standard directory assembly for the aforementioned models is also available. This assembly includes a stainless steel face frame, a clear polycarbonate directory lense and a directory backer. The directory assembly is fastened to the faceplate with McGard® security screws.

13.56MHz SMART CARD READER

A U.S. General Services Administration (GSA) approved Smart Card reader (not shown) can be ordered as a second opening option. The rugged, weatherized polycarbonate reader was designed to withstand harsh environments; provides reliable performance and resistance to vandalism. Besides being based on ISO interoperability the card reader is compatible with many popular technologies (ISO 15693, ISO 14443A and ISO 14443B), the reader also features low power consumption, 64-bit authentication to manage all RF data transmission, and Lifetime warranty against material defects and workmanship.

