

# **IP2500 Series**

# **Product Sheet**




IP2500-s Single button surface mounted



IP2500-d
Dual button
surface mounted



IP2501-s
Single button
flush mounted
with mounting box





### **IP2500 SPEAKERPHONE**

The evolution of Code Blue Corporation continues with the introduction the IP2500, a full duplex VoIP speakerphone. Ideal for both indoor and outdoor locations, these phones will allow customers to have all of their communication needs on a single platform when implemented with our signature Help Points. Code Blue has a full range of emergency phone sizes that are suitable for nearly any application.

The Code Blue IP2500 Series is an easily identifiable, vandal resistant communications device that is Americans with Disabilities Act (ADA) compliant. The quality IP2500 is hands-free, with an optional remote-mounted blue strobe/beacon that serves to identify the unit from a great distance.

It would be hard to find another phone that combines such a unique mix of features - full duplex VoIP, SIP standards, auxiliary output and outdoor rating - in one package.

# STANDARD FEATURES

- ▶ Full duplex speakerphone, intercom and paging device
- ▶ 1MB memory storage for phone numbers and audio messages
- ▶ Phone numbers up to 255 digits long
- ► SIP/IAX2 Protocol support
- ► STUN client for NAT transversal
- ▶ UDP, TCP and TLS
- ▶ 1 x IEEE 802.3u 10/100 Ethernet port
- ► Embedded web server
- Security includes:
  - HTTPS
  - Transport Layer Security (TLS)
  - SRTP (RFC3711), SIPS
  - RTCP
  - VLAN
  - · Password protection
- ▶ DTMF inband/out of band/INFO
- ▶ 2 Active Touch™ data button inputs
- ▶ 1 auxiliary N.O. output contact closures with programmable timing capability
- Self-monitoring and fault reporting:
  - · Communication service
  - · Button failure
  - Speaker failure
  - · Microphone failure


# **OPTIONAL FEATURES**

- ► Also available in flush mount
- Custom large bezel overlay options available
- ▶ Remote mount beacon/strobe

# **IP2500 Series**

# **Product Sheet**

# **DESIGN FEATURES**



# CONSTRUCTION NOTE: A standard 1/4" T-10 Torx tamperproof insert bit is needed to access unit.

- Model 2500 series 16 gauge stainless steel housing and backplate.
- Model 2501 series 12 gauge stainless steel faceplate assembly. Flush mounting box is 14 gauge painted steel.
- Electronic boards are conformal coated for outdoor operation.

# SURFACE MOUNT FLUSH MOUNT PISH HIR HL PI